



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

RF Exposure evaluation

Report Reference No.....: CTA26032302202

FCC ID.....: 2A7J2-GUTWSG3H

Compiled by

(position+printed name+signature) .: File administrators Zoey Cao

Supervised by

(position+printed name+signature) .: Project Engineer Ace Chai

Approved by

(position+printed name+signature) .: RF Manager Eric Wang

Date of issue: May 25, 2026

Testing Laboratory Name.....: Shenzhen CTA Testing Technology Co., Ltd.

Address: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name.....: CG Mobile SAS

Address: 39 rue de Courcelles, Paris, 75008 France

Standard.....: 47CFR §1.1310

47CFR §2.1093

KDB447498 D01 General RF Exposure Guidance v06

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: TRUE WIRELESS EARPHONES

Trade Mark: GUESS, DKNY, KARL LAGERFELD, HELLO KITTY

Manufacturer: Shenzhen Jsound Technologies Co., Limited

Model/Type reference: TJG03

Listed Models: See page 2

Rating: Rechargeable Li-ion Battery DC 3.7V

Result: PASS

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

TEST REPORT

Equipment under Test : TRUE WIRELESS EARPHONES

Model /Type : TJG03

Listed Models : TJG03 GUTWSG03HGCSMK, TJG03 GUTWSG03HGCSMR,
TJG03 GUTWSG03HGCSMLP, TJG03 GUTWSG03HGCSMP,
TJG03 GUTWSG03HGCSMW, TJG03 GUTWSG03HGCSME,
TJG03 GUTWSG03HGCSMO, TJG03 GUTWSG03HGCSMB,
TJG03 GUTWSG03HGCSMU, TJG03 GUTWSG03HGCSMT,
TJG03 GUTWSG03HGCSMF, TJG03 GUTWSG03HGCSMI,
TJG03 GUTWSG03HGCSMA, TJG03 GUTWSG03HGCTMK,
TJG03 GUTWSG03HGCTMLP, TJG03 GUTWSG03HGCTMR,
TJG03 GUTWSG03HGCTMP, TJG03 GUTWSG03HGCTMW,
TJG03 GUTWSG03HGCTME, TJG03 GUTWSG03HGCTMO,
TJG03 GUTWSG03HGCTMB, TJG03 GUTWSG03HGCTMU,
TJG03 GUTWSG03HGCTMT, TJG03 GUTWSG03HGCTMF,
TJG03 GUTWSG03HGCTMI, TJG03 DKTWS6G03PSLPTK,
TJG03 DKTWS6G03PSLPTE, TJG03 DKTWS6G03PSLPTP,
TJG03 DKTWS6G03PSLPTU, TJG03 DKTWS6G03PSLPTF,
TJG03 DKTWS6G03PSLPTV, TJG03 DKTWS6G03PSLP SK,
TJG03 DKTWS6G03PSLPSE, TJG03 DKTWS6G03PSLPSP,
TJG03 DKTWS6G03PSLPSU, TJG03 DKTWS6G03PSLP SF,
TJG03 DKTWS6G03PSLP SV, TJG03 KLTWSTG03IKPK,
TJG03 KLTWSTG03IKPG, TJG03 KLTWSTG03IKPO,
TJG03 KLTWSTG03IKPV, TJG03 KLTWSTG03IKPP,
TJG03 KLTWSTG03IKPU, TJG03 KLTWSTG03KCPK,
TJG03 KLTWSTG03KCPG, TJG03 HKTWSTG03KSPK,
TJG03 HKTWSTG03KSPG, TJG03 HKTWSTG03KSPO,
TJG03 HKTWSTG03KSPP, TJG03 HKTWSTG03KS PU,
TJG03 GUTWSG3HGECK, TJG03 GUTWSG3HGE CU,
TJG03 GUTWSG3HGECH, TJG03 GUTWSG3HGE CP,
TJG03 GUTWSG3HGE CR, TJG03 GUTWSG3HGE CS,
TJG03 GUTWSG3HGE CD, TJG03 GUTWSG3HGE C BD,
TJG03 GUTWSG3HGE CLB, TJG03 GUTWSG3HGE CW,
TJG03 GUTWSG3HGESK, TJG03 GUTWSG3HGES U,
TJG03 GUTWSG3HGES H, TJG03 GUTWSG3HGES P,
TJG03 GUTWSG3HGES R, TJG03 GUTWSG3HGES S,
TJG03 GUTWSG3HGES D, TJG03 GUTWSG3HGES B D,
TJG03 GUTWSG3HGES LB, TJG03 GUTWSG3HGES W,
TJG03 GUTWSG3HGETK, TJG03 GUTWSG3HGET U,
TJG03 GUTWSG3HGET H, TJG03 GUTWSG3HGET P,
TJG03 GUTWSG3HGET R, TJG03 GUTWSG3HGET S,
TJG03 GUTWSG3HGET D, TJG03 GUTWSG3HGET B D,
TJG03 GUTWSG3HGET LB, TJG03 GUTWSG3HGET W

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

Model difference : The PCB board, circuit, structure and internal of these models are the same, only model number, trade mark and colour are different for these model. So the tests were performed on model TJG03 and the test results for the main test model can cover the listed models.

Applicant : CG Mobile SAS

Address : 39 rue de Courcelles, Paris, 75008 France

Manufacturer : Shenzhen Jsound Technologies Co., Limited

Address : RM 401, 601, Building 13, No.23, Songshanzai Rd, Xinhe Community, Fucheng Street, Longhua, Shenzhen, China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1	TEST STANDARDS	5
2	SUMMARY	6
2.1	General Remarks	6
2.2	Product Description	6
2.3	Special Accessories	6
2.4	Modifications	6
3	TEST ENVIRONMENT	7
3.1	Address of the test laboratory	7
3.2	Test Facility	7
3.3	Statement of the measurement uncertainty	7
4	Test limit	8
4.1	Requirement	8
4.2	Conducted Power Results	8
4.3	Manufacturing tolerance	9
4.4	Evaluation Result	9
4.5	Simultaneous Transmission for SAR Exclusion	9
5	Conclusion	9

1 TEST STANDARDS

The tests were performed according to following standards:

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Mar. 23, 2026
Testing commenced on	:	Mar. 23, 2026
Testing concluded on	:	May 25, 2026

2.2 Product Description

Product Name:	TRUE WIRELESS EARPHONES
Model/Type reference:	TJG03
Power supply:	DC 5V(Adapter Input AC 120V/60Hz) or Rechargeable Li-ion Battery DC 3.7V
Testing sample ID:	CTA260323022-1# (Engineer sample) CTA260323022-2# (Normal sample)
Bluetooth :	
Supported Type:	Bluetooth BR/EDR
Modulation:	GFSK, $\pi/4$ DQPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Chip Antenna
Antenna gain:	2.7dBi

2.3 Special Accessories

The following is the EUT test of the auxiliary equipment provided by the laboratory:

Description	Manufacturer	Model	Technical Parameters	Certificate	Provided by
Adapter	/	HW-100225C00	Input: AC100-240V 50/60Hz 0.75A Output: DC5V 2A, DC9V 2A, DC 10V 2.25A	/	laboratory

2.4 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community,
Fuhai Street, Bao'an District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 517856 Designation Number: CN1318

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

ISED#: 27890 CAB identifier: CN0127

Shenzhen CTA Testing Technology Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

3.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.02 dB	(1)
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Output Peak power	30MHz~18GHz	0.55 dB	(1)
Power spectral density	/	0.57 dB	(1)
Spectrum bandwidth	/	1.1%	(1)
Radiated spurious emission (30MHz-1GHz)	30~1000MHz	4.10 dB	(1)
Radiated spurious emission (1GHz-18GHz)	1~18GHz	4.32 dB	(1)
Radiated spurious emission (18GHz-40GHz)	18-40GHz	5.54 dB	(1)
Time	/	±2%	(1)

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

4 Test limit

4.1 Requirement

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: “Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³ “

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} \text{ (GHz)}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

4.2 Conducted Power Results

Type	Channel	Output power (dBm)
GFSK	00	2.85
	39	2.33
	78	2.44
$\pi/4$ DQPSK	00	3.86
	39	3.28
	78	3.44

4.3 Manufacturing tolerance

Mode	Max. Conducted Output Power (dBm)	Max. tune-up
BR/EDR	3.86	3.0±1

4.4 Evaluation Result

Evaluation Results

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power (including tune-up tolerance)		SAR Test Exclusion Threshold	SAR Test Exclusion Threshold Limit	SAR Test Exclusion
			dBm	mW			
BR/EDR	2.402	5	4.0	2.5119	0.7786	3.0	Yes

4.5 Simultaneous Transmission for SAR Exclusion

N/A

5 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01v06

***** End of Report *****